CAMERA SYSTEMS

Randolph, NJ 07869 USA +1 973-448-7556 www.peerlesscreations.com

Peerless Creations LLC



Micro PTZ

29mm dia. x 83mm long 720p HD camera LED illumination Stainless steel housing Splashproof 270° pan & 95° tilt range *Digital zoom 4x Toolless focus




PTZ-35

35mm dia. x 165mm long 1080p HD camera LED illumination Stainless steel housing Waterproof 360° pan & 180° tilt range *Digital zoom 4x Easy clean decon. surfaces



PTZ-45

45mm dia. x 130mm long 1080p HD camera LED illumination Nickel plated Aluminum housing Waterproof 360° pan & 270° tilt *Digital zoom 4x



PTZ-XDMCU DVR Controller

- Built-in viewing device
- Joystick for pan, tilt, and light control
- Locking power and camera connectors
- HDMI and CVBS output
- Video recording
- Image capture
- On-board storage (micro-SD)
- Works with all PTZ-XD series camera heads
- More...



© 2023 Peerless Creations LLC.

This document provides technical information for the user. Peerless Creations LLC. reserves the right to modify the information in this document as necessary without notification. Peerless Creations LLC. holds no responsibility for any errors that may appear in this document.



Peerless Creations LLC 7 Middlebury Blvd Unit 5 Randolph, NJ 07869 USA +1 973-448-7556 www.peerlesscreations.com SERIES CAMERA SYSTEM SPECIFICATIONS

Controller Model:	PTZ-XDMCU	
Compression Format	H.264/H.265	
Illumination Control	Yes	PFRLESS* CREATIONS LLC
Video Format	MP4 (H265+AAC)	
Frame Rate	60fps	P
Data Storage	Micro SD 128GB Max	N N
Photo Format	JPG/JPEG	· ·
Image Resolution	Up to 8MP	SE
Image Capture	Yes	PTZ- D
HDMI Video Resolution	1920 X 1080	Sansonnotan
CVBS Video Resolution	720 X 576	
Operating Temperature	-30°C~70°C	
Power Supply	DC IN 12V < 1.5 A	- Smo
System Language	Chinese/English/German/Spanish/Polish/French	

Camera Model:	Micro PTZ	PTZ-35	PTZ-45
Image Sensor	1/4.4 Color CMOS	1/2.8 Color HD CMOS	
Effective Image Area	3.6mm X 2.03mm	12mm X 9.3mm	
Effective Pixel Array	1284H X 724V	1945H X 1097V	
Pixel Size	2.8µm X 2.8µm	2.8µm X 2.8µm	
Signal/Noise Ratio	>43.1dB	>30dB	
Back Light Compensation	Auto		
White Balance	Auto		
Min Illumination	.001Lux	.0001Lux/1.2F	
Wide Dynamic Range	Auto WDR		
LED Illumination	Yes		
Operating Temperature	-40°C~85°C	-30°C~85°C	
Cable Length	Up to 30 meters [100']	Up to 60 meters [200']	
Resolution	720p	1080p	







© 2023 Peerless Creations LLC.

This document provides technical information for the user. Peerless Creations LLC. reserves the right to modify the information in this document as necessary without notification. Peerless Creations LLC. holds no responsibility for any errors that may appear in this document.

